

DISCLAIMER

This brochure has been prepared specifically for customers of the publisher and as a general reference only. B&R Enclosures Pty Ltd engages in a policy of continuous development and improvement of its products and reserves the right to alter, add and/or delete specifications of any products or equipment and change of manufacturing location without notice and without incurring liability. The publisher and any party associated with the production of this catalogue do not accept any responsibility or liability whatsoever (to the extent permitted by law) for any inaccuracy, error, misinformation or misleading statements, whether negligently caused or otherwise, contained in this publication. This publication is protected by copyright and may not be reproduced or copied (using any method of reproduction or copying), sold, transmitted, circulated or otherwise forwarded to third parties, in whole or part, without prior written consent of the author. All registered trademarks and product names appearing herein are the property of the respective owners.



TABLE OF CONTENTS

Company Information

| About B&R Enclosures | 4 |
|------------------------------------|----|
| Our Locations | 5 |
| Our Capabilities | 6 |
| Our Supply Strategies | 6 |
| Customisable Project Services | 7 |
| B&R Engagement Loop | 8 |
| Our Customers | 9 |
| Accreditations and Compliance | 9 |
| Product Solutions | |
| Control Stations | 10 |
| Connector TEMF | 12 |
| Connector TE - Zinc Coated Steel | 14 |
| Connector TE - 316 Stainless Steel | 16 |

About B&R Enclosures

Since 1955, B&R Enclosures has built a reputation for excellence in design and production, culminating in our position as Australia's largest enclosure manufacturer and electrical equipment integration specialist.

As an independent, 100% Australian family owned and operated business, we champion the virtues of quality, innovation, service and value. The emphasis on these aspects has sustained B&R's growth leading to Australian manufacturing and distribution facilities in Brisbane, Adelaide and Sydney and internationally in China and Saudi Arabia.

B&R's knowledge, precision, quality and unwavering commitment to creating repeatable solutions for our clients supports our position as preferred manufacturer for many private, government and commercial projects in some of Australia's harshest environments.

Our unrivalled industry and application knowledge puts us in a unique position to meet the needs of our clients. The business encompasses four divisions: Industrial, Data ICT, Hazardous Areas and Residential Commercial. Each division focuses on the unique needs of different market segments.

B&R regularly works with partners to provide integrated solutions for major infrastructure and mining projects. These include 'plug and play' switchboard solutions for Rio Tinto's Oyu Tolgoi mine, control stations for Ichthys on-shore LNG processing plant and Australia's NBN Rollout. Ongoing relationships and collaboration are results of our ability to articulate the customer's problem and combine previous experience and knowledge with compliance to local standards.

Electrical integration involves the installation, commissioning and testing of 3rd party components and we are adept at managing the acquisition and storage of technical components through a global supply chain that is structured, customised, agile, repeatable and results-based.


Project management and execution is effectively managed at B&R by the co-location of design, supervision, supply coordination and quality control along with manufacturing. Our incorporation of Industry 4.0 delivers real-time data to our project management teams, built around the requirements of individual projects.

Extensive investment in research and development includes an environmental testing facility focussing on climate control to support cooling solutions for equipment exposed to high ambient temperatures and solar radiation.

When utilised as designed, B&R's enclosures are built to out-perform against expectations.


Contact us today to find out how B&R can deliver reliable and trusted outcomes for your project.













Our Locations



B&R Enclosures have purpose-built manufacturing facilities in three locations across Australia, as well as strategic locations in the Gulf and China.



Australia

Brisbane (QLD)

Global head office, manufacturing, sales and warehousing

Sydney, NSW

Hazardous manufacturing, sales and warehousing

Adelaide, SA

Manufacturing, sales and warehousing

Townsville (QLD), Newcastle (NSW), Melbourne (VIC), Perth (WA) Sales and warehousing

Launceston (TAS), Darwin (NT)
Distribution

New Zealand

Auckland

Sales and warehousing

Saudi Arabia

Dammam

Hazardous manufacturing, sales and warehousing

China

Suzhou

Manufacturing, sales and warehousing

Southeast Asia

Kuala Lumpur

Hazardous manufacturing, sales and warehousing

Our Capabilities

Over the years as the company has grown, we have invested significantly in machinery, technology and testing to be able to provide capabilities which our customers benefit from in every order they place. Our current capabilities include:

- Purpose-built Australian facilities in Brisbane (18,000m²), Adelaide (4,000m²) and Sydney (1,874m²), providing local labour and logistics
- Complete in-house design and engineering services to assist with creating custom solutions
- End-to-end manufacturing, from coiled steel raw material to commissioning the end product, we provide efficiency and complete quality control
- Variety of substrates and high quality finishes including stainless steel, powder coated and zinc to suit even the most demanding application
- Modern machinery for any design to be formed and fabricated including automated sheet metal panel benders, punching and shearing centres, electrical equipment integration lines, press brakes, powder coat lines, fabrication cells and assembly lines
- Fully documented process available with full configuration management to support a detailed documentation experience
- Complete project management including supply chain, warehousing and logistics
- In-house and external testing for hazardous area electrical equipment and impact, IP, type testing, static load, seismic, wind load, salt spray, line inspection, shock, vibration, EMC and MIL-STD
- Continuous improvement with our environmental testing facility for ongoing research and development
- Existing supply agreements with leading OEMs and major raw products distributors supporting loyal and valued relationships.

Our Supply Strategies



Made to Stock

These products are available ex stock from all our sales & warehousing branches. Contact your local sales representative to discuss requirements.



Assembled-to-Order

These products are assembled to order upon receipt of a customer order. All components required to build an ATO item cannot be sold separately and must form part of a kit. Standard lead time is 4-6 weeks from date of order.



Made to Order

These products are manufactured according to a customer's specification. They are marked in our catalogues as "▲ Available on request" and have a standard lead time of 2-3 weeks.



Engineered-to-Order

These products are a custom designed product that is 100% fit-for-purpose, delivered on-site and ready for installation. Our design & engineering team can customise an enclosure to suit the application requirements. Contact us for more information.

Customisable Project Services



Collaboration

- Convert customer requirements to product build specifications
- · Work to customer delivery schedule
- Initiate procurement or consignment of stock allocations
- Supply of equipment configuration





Complete Project Management

- One point of contact
- Responsive communication channels
- DIFOTIS Delivered In Full On Time In Specification
- Accountability for the delivery of our commitment to customers

Electrical & Equipment Integration

- · Wiring and equipment installed to exact requirements
- Management of free issue, consigned and/or B&R sourced components and equipment
- · Stock reporting and job allocation





Testing & Reporting To Customer Specifications

- · Digital reports of product testing and acceptance
- Serialised codes to customer requirements, digital signature, component traceability and unique indentifiers
- Real time quality assurance authorisation, approval and confirmation

Customer Specific Logistics

- Storage and warehouse management
- Site delivery logistics
- Option for removal of product packaging after installation











The B&R Engagement Loop

(Project Services)

In order to engage successfully with our project customer's, B&R representatives follow a structured service plan.

We take our responsibility seriously, and pride ourselves on the collaborative and open relationships we undertake with our project customers. This ensures we understand and provide value as our customer's needs vary greatly across the different types of project application and technical requirements.

- 1. Our first action before we reach out or after a customer had reached out to us. is to INVESTIGATE. This includes researching the customer/ project and any other relevant stakeholders.
- 2. The second action of **UNDERSTAND** is when we speak to the customer at length about their issue and challenges for current and future projects. From these discussions we can begin to see how our product solutions can solve the customer's issues and challenges.

- 3. We take our newly acquired customer knowledge back to our in-house design, engineering and estimating teams for our third action to SCOPE the work, and prepare quotes and drawings as required.
- 4. Once we have created the tailored offer for the customer we process any variations which might be needed before our fourth action of AGREE. With everything signed off we move into manufacturing and equipment integration.
- 5. Once the product solution is ready our fifth action of **DELIVER** takes place. We make sure the goods are shipped to site according to agreed upon timelines.
- 6. To learn from our experience and confirm our service level we take an EVALUATION action. This is when we reflect on the job we've completed and depending on the size and extent of the order we will seek customer feedback as well.



Our Customers







RioTinto





Accreditations & Compliance

At B&R, quality and value are just the beginning. We strive to deliver quality products developed and manufactured by a team dedicated to excellence, backed by standards, approvals and industry accreditations.



€ SAI GLOBAL

ISO 9001:2015

Every B&R Enclosures manufacturing facility is externally audited to ensure that the quality of our products meet the stringent ISO9001 standards. B&R's products are carefully inspected at the end of lines during the manufacturing process to ensure that the enclosures will withstand their intended environment and application.



ISO 14001:2015

Sets out the criteria for an environmental management system. It maps out a framework that a company or organisation can follow to set up an effective environmental management system.



ISO 45001:2018
An externally audited
Occupational Health and Safety
Management System.



RoHS

The RoHS directive aims to restrict certain dangerous substances commonly used in electronic equipment.



Australian Stainless Steel Development Assoc.

ASSDA

The Australian Stainless Steel Development Association provides comprehensive technical information on stainless steel. This includes information for users, equipment manufacturers and stainless steel suppliers.

Control Stations - Stainless Steel

Pushbutton Enclosures with Mounting Flanges







- · Designed to house pushbuttons in heavy duty industrial or harsh and demanding environments.
- Suitable for applications where an IP66 protection rating is required*
- Mounting flanges for ease of installation.
- Available with or without cut outs.
- Cut outs available as 22.5mm or 30.8mm.
- Up to 9 cut outs, dependent on enclosure size.
- Range of pushbuttons able to be fitted as part of the order.
- Earth stud included internally.
- Manufactured from 1.5mm thick 316 stainless steel with N4 surface finish.



ORDERING GUIDE

| ensio | |
|-------|--|
| | |
| | |

| | | | | | <u> </u> | | | | |
|-------------|--------|----------|-------|---------------|----------|---------|-------------|---------|--|
| | | External | | Internal | Mounting | Centres | | | |
| D (N) | Height | Width | Depth | Useable Depth | Height | Width | Push Button | Cable | \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\ |
| Part Number | (A) | (B) | (C) | (D) | (E) | (F) | Cut Outs | Entries | Weight (kg) |
| CS11/S | 152 | 97 | 93 | 90 | 132 | 67 | _ | _ | 1.1 |
| CS12/S | 199 | 97 | 93 | 90 | 179 | 67 | _ | - | 1.5 |
| CS13/S | 245 | 97 | 93 | 90 | 225 | 67 | _ | _ | 1.8 |
| CS14/S | 290 | 97 | 93 | 90 | 270 | 67 | _ | _ | 2.0 |
| CS16/S | 383 | 97 | 93 | 90 | 363 | 67 | _ | - | 2.7 |
| CS11/SH22 | 152 | 97 | 93 | 90 | 132 | 67 | 1 x 22mm | 1 x M20 | 1.1 |
| CS12/SH22 | 199 | 97 | 93 | 90 | 179 | 67 | 2 x 22mm | 1 x M20 | 1.5 |
| CS13/SH22 | 245 | 97 | 93 | 90 | 225 | 67 | 3 x 22mm | 1 x M25 | 1.8 |
| CS14/SH22 | 290 | 97 | 93 | 90 | 270 | 67 | 4 x 22mm | 1 x M25 | 2.0 |
| CS16/SH22 | 383 | 97 | 93 | 90 | 363 | 67 | 6 x 22mm | 1 x M25 | 2.7 |
| CS33/SH22 | 245 | 272 | 93 | 90 | 225 | 197 | 9 x 22mm | 2 x M25 | 3 |
| CS11/SH30 | 152 | 97 | 93 | 90 | 132 | 67 | 1 x 30mm | 1 x M20 | 1.1 |
| CS12/SH30 | 199 | 97 | 93 | 90 | 179 | 67 | 2 x 30mm | 1 x M20 | 1.5 |
| CS13/SH30 | 245 | 97 | 93 | 90 | 225 | 67 | 3 x 30mm | 1 x M25 | 1.8 |
| CS14/SH30 | 290 | 97 | 93 | 90 | 270 | 67 | 4 x 30mm | 1 x M25 | 2.0 |
| CS16/SH30 | 383 | 97 | 93 | 90 | 363 | 67 | 6 x 30mm | 1 x M25 | 2.7 |
| CS33/SH30 | 245 | 272 | 93 | 90 | 225 | 197 | 9 x 30mm | 2 x M25 | 3 |




Assembled product solution - dust cover (CSDC33/S), control station (CS33/SH30) and plug (CSP30/S)



CSDC33/S





CS33/SH30 and CSP30/S



CSP30/S

10


^{*}IP66 rating applies when fitted with appropriate IP rated pushbuttons or plug


Control Stations - Stainless Steel


Pushbutton Enclosures with Mounting Flanges


TECHNICAL DRAWINGS

















22.5mm cut out

30mm cut out









ACCESSORIES

| | | Din | | | |
|-------------|------------------------------|--------|-------|-------|-------------|
| Part Number | Product | Height | Width | Depth | Weight (kg) |
| CSDC1-6/S | Dust cover suitable for CS1* | 400 | 170 | 145 | 2.9 |
| CSDC33/S | Dust cover suitable for CS3* | 400 | 310 | 165 | 3.8 |
| CSP22/S | M22 Plug | - | _ | - | - |
| CSP30/S | M30 Plug | _ | _ | _ | _ |

Connector TEMF

Termination Enclosures with Mounting Flanges









- Suitable for housing terminations, pushbuttons or switchgear in industrial or demanding environments.
- Designed for applications where a smaller enclosure is required.
- Captive 316 stainless steel combo head screws to prevent loss when fastening.
- Provision for mounting DIN rails or a mounting pan, increasing application flexibility.
- Conformity, Approvals: Lloyds Register #06/10007 (E2)
- Region D wind rated to AS1170.2-2002: Structural design actions Wind actions
- Manufactured from 1.2mm thick 316 stainless steel.
- N4 surface finish.

Comes standard with:

· Earth strap kit





ORDERING GUIDE


| | Dimensions (mm) | | | | | | | | | | | |
|-------------|-----------------|--------------|--------------|----------------|--------------------|------------------|--------------|---------------|--------------|-------------|--|--|
| | | External | | Useable Depth | | Mounting Centres | | Ope | ning | | | |
| Part Number | Height (A) | Width (B) | Depth (C) | With DIN Rail* | With Mounting Pan* | Height (D) | Width (E) | Height (F) | Width (G) | Weight (kg) | | |
| TE1108MF/S | 150 | 150 | 80 | 47 | 60 | 175 | 100 | 125 | 125 | 1.4 | | |
| TE3112MF/S | 300 | 150 | 120 | 87 | 100 | 325 | 100 | 275 | 125 | 2.6 | | |
| TE2212MF/S | 200 | 200 | 120 | 87 | 100 | 225 | 150 | 175 | 175 | 2.4 | | |
| TE3212MF/S | 300 | 200 | 120 | 87 | 100 | 325 | 150 | 275 | 175 | 3.1 | | |
| TE4212MF/S | 400 | 200 | 120 | 87 | 100 | 425 | 150 | 375 | 175 | 3.8 | | |
| TE6212MF/S▲ | 600 | 200 | 120 | 87 | 100 | 625 | 150 | 575 | 175 | 5.0 | | |

Mounting pan and DIN rail are an optional extra

TECHNICAL DRAWINGS







[▲] Available on request

Connector TEMF Termination Enclosures with Mounting Flanges



| ACCESSORIES | | | | | TE1108MF/S | 2MF/S | 2MF/S | 2MF/S | 2MF/S | 2MF/S |
|---|-------------|-------------|-----------------|-------|------------|-------|-------|-------|-------|-------|
| | | | Dimensions (mm) | | | 7 | 7 | | | 2 |
| Product | Description | Part Number | Height | Width | TE1 | TE3 | TE2 | TE32 | TE42 | TE6 |
| | | TEMP11 | 123 | 120 | • | | | | | |
| Mounting pan – 2mm (powdercoated white) | | TEMP22 | 173 | 170 | | | • | | | |
| | | TEMP31 | 273 | 120 | | • | | | | |
| | Metal | TEMP32 | 273 | 170 | | | | • | | |
| | | TEMP42 | 373 | 170 | | | | | • | |
| | | TEMP62 | 573 | 170 | | | | | | |
| | | TED1 | 140 | 35 | • | | | | | |
| | | TED2 | 190 | 35 | | | • | | | |
| DIN Rail | Aluminium | TED3 | 290 | 35 | | | | • | | |
| | | TED4 | 390 | 35 | | | | | • | |
| | | TED6 | 500 | 35 | | | | | | |





Metal mounting pan

DIN Rail

Connector TE - Zinc Coated Steel

Termination Enclosures









- · Suitable for housing terminations, push buttons or switchgear in industrial or demanding environments.
- Designed for installations where smaller enclosures are required.
- Captive 316 stainless steel combo head screws, used to prevent loss when fastening.
- Provision for mounting DIN rails or a mounting pan, increasing application flexibility.
- Conformity, Approvals: Lloyds Register #06/10007 (E2)
- Manufactured from 1.2mm thick zinc coated steel.
- Powdercoated Pebble Grey RAL7032.

Comes standard with:

Earth strap kit




ORDERING GUIDE


Dimensions (mm)


| | | External | | Useable Depth | | Openir | ıg Size | • |
|-------------|------------|--------------|--------------|----------------|--------------------|------------|--------------|-------------|
| Part Number | Height (A) | Width (B) | Depth (C) | With DIN Rail* | With Mounting Pan* | Height (D) | Width (E) | Weight (kg) |
| TE1108 | 150 | 150 | 80 | 47 | 60 | 125 | 125 | 1.2 |
| TE3112 | 300 | 150 | 120 | 87 | 100 | 275 | 125 | 2.4 |
| TE2212 | 200 | 200 | 120 | 87 | 100 | 175 | 175 | 2.2 |
| TE3212 | 300 | 200 | 120 | 87 | 100 | 275 | 175 | 2.9 |
| TE4212 | 400 | 200 | 120 | 87 | 100 | 375 | 175 | 3.6 |
| TE6212 | 600 | 200 | 120 | 87 | 100 | 575 | 175 | 4.9 |

^{*} Mounting pan and DIN rail are available as optional extra

TECHNICAL DRAWINGS







Connector TE – Zinc Coated Steel

Termination Enclosures



| ACCESSORIES | | | | | | | | | | |
|--|---------------------------|-------------|-----------|----------|--------|-------|------|------|-----|------|
| | | | Dimension | ons (mm) | TE1108 | 112 | 212 | 212 | 212 | 212 |
| Product | Description | Part Number | Height | Width | TE1 | TE311 | TE22 | TE32 | TE4 | TE62 |
| | | TEMP11 | 123 | 120 | • | | | | | |
| Mounting pan – metal (powdercoated white) | | TEMP22 | 173 | 170 | | | • | | | |
| | • | TEMP31 | 273 | 120 | | ٠ | | | | |
| | 2mm | TEMP32 | 273 | 170 | | | | • | | |
| | | TEMP42 | 373 | 170 | | | | | | |
| | | TEMP62 | 573 | 170 | | | | | | |
| | | TED1 | 140 | 35 | | | | | | |
| | | TED2 | 190 | 35 | | | | | | |
| DIN Rail | Aluminium | TED3 | 290 | 35 | | • | | • | | |
| | | TED4 | 390 | 35 | | | | | | |
| | | TED6 | 590 | 35 | | | | | | |
| Wall mounting brackets – 316 stainless steel | Set of 4 (1 Tonne SWL) | MEB/S | - | - | • | | | | • | • |



Touch up paint (300g)



Pebble Grey RAL7032



TUP/P20

.

Metal mounting pan

DIN Rail

MEB/S (set of 4)

Connector TE - 316 Stainless Steel

Termination Enclosures









- Suitable for housing terminations, pushbuttons or switchgear in industrial or demanding environments.
- Designed for installations where smaller enclosures are required.
 Captive 316 stainless steel combo head screws, used to prevent loss when fastening.
- Provision for mounting DIN rails or a mounting pan, increasing application flexibility.
- Conformity, Approvals: Lloyds Register #06/10007 (E2)
- Manufactured from 1.2mm thick 316 stainless steel.
- Powdercoated N4 surface finish.

Comes standard with:

Earth strap kit





ORDERING GUIDE


| | | | - | | | | | |
|-------------|--------|----------|-------|----------------|--------------------|---------|-------|-------------|
| | | External | | Usea | Openir | ıg Size | | |
| | Height | Width | Depth | | | Height | Width | |
| Part Number | (A) | (B) | (C) | With DIN Rail* | With Mounting Pan* | (D) | (E) | Weight (kg) |
| TE1108/S | 150 | 150 | 80 | 47 | 60 | 125 | 125 | 1.2 |
| TE3112/S | 300 | 150 | 120 | 87 | 100 | 275 | 125 | 2.4 |
| TE2212/S | 200 | 200 | 120 | 87 | 100 | 175 | 175 | 2.2 |
| TE3212/S | 300 | 200 | 120 | 87 | 100 | 275 | 175 | 2.9 |
| TE4212/S | 400 | 200 | 120 | 87 | 100 | 375 | 175 | 3.6 |
| TE6212/S | 600 | 200 | 120 | 87 | 100 | 575 | 175 | 4.9 |

^{*} Mounting pan and DIN rail are available as optional extra

TECHNICAL DRAWINGS







Connector TE – 316 Stainless Steel

Termination Enclosures



ACCESSORIES

| | | | Dimensions (mm) | | | TE3112/S | 2212/S | _ | E4212/S | E6212/S |
|--|---------------------------|-------------|-----------------|-------|----------|----------|--------|---|---------|---------|
| Product | Description | Part Number | Height | Width | TE1108/S | Ä | TE22 | Ĭ | ŢĘ, | Ţ |
| Mounting pan – 2mm (powdercoated white) | | TEMP11 | 123 | 120 | • | | | | | |
| | | TEMP22 | 173 | 170 | | | • | | | |
| | Madal | TEMP31 | 273 | 120 | | • | | | | |
| | Metal | TEMP32 | 273 | 170 | | | | • | | |
| | | TEMP42 | 373 | 170 | | | | | • | |
| | | TEMP62 | 573 | 170 | | | | | | • |
| | | TED1 | 140 | 35 | • | | | | | |
| | | TED2 | 190 | 35 | | | • | | | |
| DIN Rail | Aluminium | TED3 | 290 | 35 | | • | | • | | |
| | | TED4 | 390 | 35 | | | | | • | |
| | | TED6 | 590 | 35 | | | | | | • |
| Wall mounting brackets – 316 stainless steel | Set of 4 (1 Tonne SWL) | MEB/S | - | - | • | • | • | • | • | • |







Metal mounting pan

DIN Rail

MEB/S (set of 4)

AUSTRALIA

T: 1300 Enclosures (1300 362 567) E: sales@brenclosures.com.au brenclosures.com.au

QUEENSLAND

Brisbane Manufacturing, Sales & Warehouse 51 Stradbroke Street Heathwood QLD 4110

(PO Box 1151) Browns Plains BC QLD 4118

T: +61 7 3714 1111

E: salesqld@brenclosures.com.au

NORTH QUEENSLAND

Townsville Sales & Warehouse Unit 4/ 780 Ingham Road Mount Louisa, QLD 4814 (PO Box 7615) Garbutt QLD 4814

E: salestvl@brenclosures.com.au

NEW SOUTH WALES

T: +61 7 4727 1900

NSW & ACT Sales & Warehouse 7 Metters Place Wetherill Park NSW 2164

T: +61 2 9915 9555

E: salesnsw@brenclosures.com.au

NEWCASTLE Distribution Ross Joice Agencies Pty Ltd 109-111 Broadmeadow Road

Broadmeadow NSW 2292 T: +61 2 4961 4433

VICTORIA

VIC & TAS Sales & Warehouse 50-52 Sunmore Close **Heatherton VIC 3202**

T: +61 3 9552 0552

E: salesvic@brenclosures.com.au

TASMANIA Distribution W P Martin Pty Ltd 85 Elizabeth Street

Launceston TAS 7250

T: +61 3 6331 5545

SOUTH AUSTRALIA

SA & NT Manufacturing, Sales & Warehouse 505 Grand Junction Road

Wingfield SA 5013

T: +61 8 8417 6222

E: salessa@brenclosures.com.au

NORTHERN TERRITORY Distribution Jewell Distributors Pty Ltd Cnr Hidden Valley & Beaton Roads

Berrimah NT 0828 T: +61 8 8947 0870

WESTERN AUSTRALIA

WA Sales Office & Warehouse

6 Montgomery Way Malaga WA 6090 T: +61 8 6310 4777

E: saleswa@brenclosures.com.au

NEW ZEALAND

Sales

B&R Enclosures Limited T: 0800 Enclosures (0800 362 567) E: sales@brenclosures.co.nz brenclosures.co.nz

AUCKLAND Distribution

Matchmaster Unit 6103 Cryers Road East Tamaki Auckland NZ 2013

T: +64 9 265 2097

E: sales@brenclosures.co.nz

CHRISTCHURCH Distribution

Matchmaster

17 Washbournes Road Wigram Christchurch NZ 8042

T: +64 3 348 0659

E: sales@brenclosures.co.nz

CHINA

B&R Enclosures (Suzhou) Co. Ltd E: sales@brenclosures.com.cn brenclosures.com.cn

Manufacturing, Sales & Warehouse South Block, Building 23 Chuangtou Industrial Zone Heshun Road, SIP, Suzhou 215122 PEOPLE'S REPUBLIC OF CHINA

T: +86 512 8718 2139

E: sales@brenclosures.com.cn

MIDDLE EAST

Sales

B&R Gulf

M: +966 503 496 592

T: +966 381 2869 1 or +966 5034 9659 2

E: sales@brgulf.com.sa

brgulf.com

DAMMAM Manufacturing, Sales & Warehouse

B&R Gulf

Factory No. 12, Modon Buildings, King Salman Road, Industrial Area 3,

Dammam, Saudi Arabia M: +966 503 496 592

T: +966 381 2869 1 or +966 5034 9659 2

E: sales@brgulf.com.sa

brgulf.com